

## TF40



Model: TF40

Description:

- \* 40 liters
  - \* Thermoelectric cooling
  - \* Temperature range: 5~15°C
  - \* Max Temp Reducing: 23°C below ambient
  - \* Environment Temperature N
  - \* Electric Shock Protection I
  - \* Input power: 70W
  - \* AC120V/60HZ
  - \* US plug
  - \* Safety approval: CE
- Packing & Loading:



- \* 1PC/CTN
- \* Export Standard Carton
- \* N.W.:11.8KGS G.W.:12.8KGS
- \* Product size: 410x420x540mm
- \* EC Dimension: 495x475x585mm
- \* 1\*20"GP: 132pcs
- 1\*40"GP: 368pcs
- 1\*40"HQ: 505pcs



## TCW40 40 liter



Model:TCW40

Description:

- \* 40L portable cooler/freezer
- \* Capacity:40L
- \* Approval:GS,CE,E-MARK,ROHS,SAA,
- \* Temperature range: (-5°C~+55°C),cooling to 30°C below ambient temperature
- \* Input Voltage:DC12V/24V,AC110V-230V(by AC/DC adaptor)
- \* Currency:8A ON 12V
- \* Power consumpton:96W
- \* Cooling elements:2 pcs thermoelectric module
- \* Cooling for thermoelectric:water circulation cooling
- \* Insulation:40mm Polyurethane Foaming
- \* Accessories:1 pc cover bag,instruction manual,inside cabinet basket,AC cable,DC cable
- \* LCD display, temperature set and control
- \* AC/DC transformer built-in
- \* active battery protection-automatic cut off at 10.5V
- \* stainless steel latches
- \* pre-coated metal body shell

Packing & Loading:

[www.frinko.mk](http://www.frinko.mk) [www.klimafilia.mk](http://www.klimafilia.mk) +389 47 203 900



- \* 1PC/CTN
- \* Export Standard Carton
- \* N.W.:14KGS G.W.:16KGS
- \* Product size: 562x370x539mm
- \* EC Dimension: 615x430x590mm
- \* 1\*20"GP: 204pcs
- 1\*40"GP: 408pcs
- 1\*40"HQ: 416pcs



## TCW30 30 liter



Model:TCW30

Description:

- \* 30L portable cooler/freezer
- \* Capacity:30L
- \* Approval:GS,CE,E-MARK,ROHS,SAA,
- \* Temperature range: (-5°C~+55°C),cooling to 30°C below ambient temperature
- \* Input Voltage:DC12V/24V,AC110V-230V(by AC/DC adaptor)
- \* Current:8A ON 12V
- \* Power consumption:96W
- \* Cooling elements:2 pcs thermoelectric module
- \* Cooling for thermoelectric:water circulation cooling
- \* Insulation:40mm Polyurethane Foaming
- \* Accessories:1 pc cover bag,instruction manual,inside cabinet divider,AC cable,DC cable
- \* LCD display, temperature set and control
- \* AC/DC transformer built-in
- \* active battery protection-automatic cut off at 10.5V
- \* stainless steel latches
- \* pre-coated metal body shell

Packing & Loading:

[www.frinko.mk](http://www.frinko.mk) [www.klimafilia.mk](http://www.klimafilia.mk) +389 47 203 900



- \* 1PC/CTN
- \* Export Standard Carton
- \* N.W.:12KGS G.W.:14KGS
- \* Product size: 562x370x415mm
- \* EC Dimension: 615x430x475mm
- \* 1\*20"GP: 242pcs
- 1\*40"GP: 492pcs
- 1\*40"HQ: 518pcs