



## T-SY600 Series Stainless Steel Solenoid Valve. N.C & N.O, 2/2 way

T-SY600 Series Stainless Steel Solenoid Valve. N.C & N.O, 2/2 way



Product code : T-SY600

Brand : TORQ

### T-SY600 Series Stainless Steel Solenoid Valve. N.C & N.O, 2/2 way

#### TORQ Stainless Steel Scylindrical Body Solenoid Valves. 2/2 way

T-SY600 Series	:	normally closed, normally open positions
Application	:	air, water, acid, aggressive media
Voltage	:	230, 220V, 110V, 24V, 12V AC, 24V, 12V DC
specify coil voltage with order		
Protection Class	:	IP 65 with plug
Seal	:	FKM, PTFE
On Request	:	high pressure body valve
Way	:	2/2 way
Orifice	:	2,5 mm (on request: 1mm, 1,8mm, 4mm, 7mm)
Tube, Internal Parts	:	stainless steel

Size	Order Types	Orifice	Kv	Pressure(bar)	Temp. (°C)	Body	Seal	Net Weight
G	T-SY Series	(mm)	(lt/min)	Min Max	Min Max	Brass	---	(kg)
1/8"	T-SY 600	2,5	3,2	0.....12	-10.....160	stainless steel	PTFE	0,46

EL

News

ΕΛΛΗΝΙΚΗ  
**Electrolux**  
 Macedonia  
 Palenzo

1/8"	T-SY 600.1,8	1,8	1,6	0.....16	-10.....160	stainless steel	PTFE	0,46
1/8"	T-SY 600.3	3	4,6	0.....10	-10.....160	stainless steel	PTFE	0,46
1/8"	T-SY 600.4	4	6,4	0.....9	-10.....160	stainless steel	PTFE	0,46
1/8"	T-SY 600.5	5	9,2	0.....7	-10.....160	stainless steel	PTFE	0,46
1/8"	T-SY 600.6	6	11	0.....6	-10.....160	stainless steel	PTFE	0,46
1/4"	T-SY 601	2,5	3,2	0.....12	-10.....160	stainless steel	PTFE	0,45
1/4"	T-SY 601.1,8	1,8	1,6	0.....16	-10.....160	stainless steel	PTFE	0,45
1/4"	T-SY 601.3	3	4,6	0.....10	-10.....160	stainless steel	PTFE	0,45
1/4"	T-SY 601.4	4	6,4	0.....9	-10.....160	stainless steel	PTFE	0,45
1/4"	T-SY 601.5	5	9,2	0.....7	-10.....160	stainless steel	PTFE	0,45
1/4"	T-SY 601.6	6	11	0.....6	-10.....160	stainless steel	PTFE	0,45
3/8"	T-SY 602.5	5	9,2	0.....7	-10.....160	stainless steel	PTFE	0,42
3/8"	T-SY 602	7	12,4	0.....5	-10.....160	stainless steel	PTFE	0,42



## T-SY.3W600 Series Stainless Steel Solenoid Valves. N.C, 3/2 way

T-SY.3W600 Series Stainless Steel Solenoid Valves. N.C, 3/2 way



Product code : T-SY.3W 600

Brand : TORQ

### T-SY.3W600 Series Stainless Steel Solenoid Valves. N.C, 3/2 way

[TORQ Solenoid Valves, Stainless Steel, Scylindrical Shape, 3/2 way](#)

[T-SY.3W600 Series](#) normally closed, positions (on request: N.O position)

Application :	air, water, acid, aggressive media, oil
Voltage :	230, 220V, 110V, 24V, 12V AC, 24V, 12V DC
specify coil voltage with order.	
Protection Class :	IP 65 with plug
Seal :	FKM, PTFE
On Request :	high pressure body valve
Way :	3/2 way
Tube, Internal Parts :	stainless steel

Size	Order Types	Orifice	Kv	Pressure	Temp.	Body	Seal	Weight
G	T-SY Series	(mm)	(lt/min)	Min	Max	Min	Max	Brass
1/8"	T-SY.3W 600	2,5	1-2=2,7, 2-3=2,7	0.....10	-10....160	stainless steel	VITON	0,46
1/8"	T-SY.3W 600.1,8	1,8	1-2=1,35, 2-3=2,7	0.....12	-10....160	stainless steel	VITON	0,46



1/4" T-SY.3W 601	2,5	1-2=2,7, 2-3=2,7	0.....10	-10....160	stainless steel	VITON	0,45
1/4" T-SY.3W 601.1,8	1,8	1-2=1,35, 2-3=2,7	0.....12	-10....160	stainless steel	VITON	0,45



## T-SK600 Series Stainless Steel Solenoid Valves 2/2 way, N.C & N.O

T-SK600 Series Stainless Steel Solenoid Valves 2/2 way, N.C & N.O



Product code : T-SK600 Serisi

Brand : TORK

### T-SK600 Series Stainless Steel Solenoid Valves 2/2 way, N.C & N.O

[TORK, Stainless Steel Solenoid Valves 2/2 way](#)

[T-SK600 Series](#)

normally closed, normally open position

Application : air, water, acid, aggressive media

Body : square shape , stainless steel

Voltage : 230, 220V, 110V, 24V, 12V AC, 24V, 12V DC  
specify coil voltage with order

Protection Class : IP 65 with plug

Seal : FKM, PTFE

On Request : high pressure body valve

Way : 2/2 way

Tube, Internal Parts : stainless steel

N.C position

Size	Order Types	Orifice	Kv	Pressure(bar)	Temp. (°C)	Body	Seal	Net Weight
G	T-SK Series	(mm)	(lt/min)	Min Max	Min Max	Brass	---	(kg)
1/8"	T-SK 600	1,6	1,6	0.....16	-10.....160	stainless steel	PTFE	0,44

EL

News

 Електролюкс  
 Electrolux  
 Macedonia  
 Palenzo

1/8"	T-SK 600.2,5	2,5	3,2	0.....12	-10.....160	stainless steel	PTFE	0,44
1/8"	T-SK 600.3	3	4,6	0.....10	-10.....160	stainless steel	PTFE	0,44
1/8"	T-SK 600.4	4	6,4	0.....9	-10.....160	stainless steel	PTFE	0,44
1/8"	T-SK 600.5	5	9,2	0.....7	-10.....160	stainless steel	PTFE	0,44
1/8"	T-SK 600.6	6	11	0.....6	-10.....160	stainless steel	PTFE	0,44
1/4"	T-SK 601	1,8	1,6	0.....16	-10.....160	stainless steel	PTFE	0,43
1/4"	T-SK 601.2,5	2,5	3,2	0.....12	-10.....160	stainless steel	PTFE	0,43
1/4"	T-SK 601.3	3	4,6	0.....10	-10.....160	stainless steel	PTFE	0,43
1/4"	T-SK 601.4	4	6,4	0.....9	-10.....160	stainless steel	PTFE	0,43
1/4"	T-SK 601.5	5	9,2	0.....7	-10.....160	stainless steel	PTFE	0,43
1/4"	T-SK 601.6	6	11	0.....6	-10.....160	stainless steel	PTFE	0,43
3/8"	T-SK 602	5	9,2	0.....7	-10.....160	stainless steel	PTFE	0,42
3/8"	T-SK 602.6	6	11	0.....6	-10.....160	stainless steel	PTFE	0,42
3/8"	T-SK 602.7	7	12,4	0.....5	-10.....160	stainless steel	PTFE	0,42
3/8"	T-SK 602.8	8	13,5	0.....3	-10.....160	stainless steel	PTFE	0,42
3/8"	T-SK 602.9	9	16	0.....2	-10.....160	stainless steel	PTFE	0,42
3/8"	T-SK 602.10	10	19	0.....1	-10.....160	stainless steel	PTFE	0,42
1/2"	T-SK 603	7	12,4	0.....5	-10.....160	stainless steel	PTFE	0,41
1/2"	T-SK 603.5	5	9,2	0.....7	-10.....160	stainless steel	PTFE	0,41
1/2"	T-SK 603.6	6	11	0.....6	-10.....160	stainless steel	PTFE	0,41
1/2"	T-SK 603.8	8	13,5	0.....3	-10.....160	stainless steel	PTFE	0,41
1/2"	T-SK 603.9	9	16	0.....2	-10.....160	stainless steel	PTFE	0,41
1/2"	T-SK 603.10	10	19	0.....1	-10.....160	stainless steel	PTFE	0,41
3/4"	T-SK 604	5	9,2	0.....7	-10.....160	stainless steel	PTFE	0,79

EL

News

Electrolux  
Macedonia  
Palenzo

3/4"	T-SK 604.6	6	11	0.....6	-10.....160	stainless steel	PTFE	0,79
3/4"	T-SK 604.7	7	12,4	0.....5	-10.....160	stainless steel	PTFE	0,79
3/4"	T-SK 604.8	8	13,5	0.....3	-10.....160	stainless steel	PTFE	0,79
3/4"	T-SK 604.9	9	16	0.....2	-10.....160	stainless steel	PTFE	0,79
3/4"	T-SK 604.10	10	19	0.....1	-10.....160	stainless steel	PTFE	0,79
1"	T-SK 605	5	9,2	0.....7	-10.....160	stainless steel	PTFE	0,77
1"	T-SK 605.6	6	11	0.....6	-10.....160	stainless steel	PTFE	0,77
1"	T-SK 605.7	7	12,4	0.....5	-10.....160	stainless steel	PTFE	0,77
1"	T-SK 605.8	8	13,5	0.....3	-10.....160	stainless steel	PTFE	0,77
1"	T-SK 605.9	9	16	0.....2	-10.....160	stainless steel	PTFE	0,77
1"	T-SK 605.10	10	19	0.....1	-10.....160	stainless steel	PTFE	0,77



**T-SY.3W600 Series Stainless Steel Solenoid Valves 3/2 way**

TORK, Stainless Steel Solenoid Valves (size: 1/8".....1/4")

T-SK.3W600 Series

3/2 way normally closed

- Application : air, water, acid, aggressive media
- Voltage : 230, 220V, 110V, 24V, 12V AC, 24V, 12V DC
- specify coil voltage with order
- Protection Class : IP 65 with plug
- Seal : FKM, PTFE
- On Request : high pressure body valve
- Way : 3/2 way
- Tube, Internal Parts : stainless steel

Size	Order Types	Orifice (mm)	Kv (lt/min)	Pressure Min	Pressure Max	Temp. Min	Temp. Max	Body	Seal	Weight (kg)
1/8"	T-SY.3W 600	2,5	1-2=2,7, 2-3=2,7	0.....10		-10.....160		stainless steel	VITON	0,46
1/8"	T-SY.3W 600.1,8	1,8	1-2=1,35, 2-3=2,7	0.....12		-10.....160		stainless steel	VITON	0,46
1/4"	T-SY.3W 601	2,5	1-2=2,7, 2-3=2,7	0.....10		-10.....160		stainless steel	VITON	0,45
1/4"	T-SY.3W 601.1,8	1,8	1-2=1,35, 2-3=2,7	0.....12		-10.....160		stainless steel	VITON	0,45





## T-SYD600 Serisi pilot kontrollü solenoid valf

T-SYD600 Serisi pilot kontrollü solenoid valf



Product code : T-SYD600

Brand : TORK