



LINAX

Floor stripper









Ingredients:

LINAX contains: less than 5% anionic surfactants, nonionic surfactants, less than 5% NTA, fragrance. Other ingredients: water soluble solvents. pH-value: approx. 11.

Performance:

ffortlessly removes old, heavily worn wax and polymer films. Extremely well suited to sensitive coverings such as linoleum and rubber. Can be mixed with water in any proportion. No unpleasant odour during and after application. Takes effect quickly, low foaming and high material compatibility. Virtually non-slip during stripping.

Application notes:

All kinds of floorings. Exception: unsealed wooden floors.

Usage:

Depending on the nature and thickness of the dirt and care products to be removed, apply to the floor neat or diluted with water to as much as 1:10. Leave to take effect for 10 min. and work with a scrubber or floor machine. Pick up dissolved dirt and film residues. Wipe off when wet. It is advisable to work on small sections at a time.

Precautions for use:

During the application, ensure adequate ventilation of the room. Keep container tightly closed and out of reach of children. Do not let loose dirt or film rests dry again.

Ecology:

This product is subject to regulations governing the environmental compatibility of washing and cleaning agents and the associated regulations on the biological degradability of the raw materials used.

Comprehensive information on the environmental characteristics of this product is available on request.

Give only completely emptied packaging to special waste disposer.

This product is designated for industrial use.

Product code: GG 20

UBA 0947 0197

Waste Key: 070608

ArtNr.: 04663	200 l
ArtNr.: 04744	10





