

DOMETIC COMFORT



NEW

■ Midi-Heki

With crank or electronic version

THE NEW DIMENSION FOR HIGHEST HANDLING COMFORT

The Midi-Heki not only offers perfect incidence of light and exceptional quality, but also very easy handling and highest comfort for perfect air distribution – thanks to the new crank and electronic versions.

Blind and fly-net are guided on the sides with a pole to allow perfect adjustment. Both are seamlessly adjustable and can be operated independently of each other. The cut-out dimensions of 700 x 500 mm are the same as with the Midi-Heki with operating bar.

Crank and electronic version at accessories trade from January 2005

 **Dometic**





NEW

■ Midi-Heki

Electronic version



Crank version



Highly efficient dimming

The inner frame is equipped with a black pleated fly-net and a single-pleated blind. For cleaning the inner frame can be easily detached and re-mounted.

The fabric is aluminium coated on the outside to reflect infrared rays and non-transparent to guarantee maximum privacy.



Closed



Completely open

www.dometic.com.

Seitz GmbH & Co. KG
 Altkrautheimer Straße 28
 D-74238 Krautheim/Jagst
 Tel.: + 49 62 94/907-0
 Fax: + 49 62 94/907-40

All advantages at a glance

- Double-glazed glass dome made of acrylic glass which is tinted light grey
- Inner and outer pane are glued together which makes them leak-proof, stable and easy to clean.
- Three positions possible: completely open, half open and ventilation position.
- Big glass overlap on the sides and the outer frame pointing upwards prevent penetration of water inside when the dome is in ventilation position.
- The dome is automatically locked when closed.
- The frame is made of durable, weatherproof ASA
- Available with or without fixed ventilation
- Blind and fly-net are seamlessly adjustable
- Cut-out dimensions: 700 x 500 mm
- Clearance: 585 x 404 mm for maximum incidence of light
- Easy installation in roofs with a thickness of 25 to 60 mm – various installation sets available
- Weight: 7,6 kg with lever, 9,3 kg with crank, 8,4 kg with electronic handling

