

RH HALF SECTIONS										
HEATER DIMENSIONS			1850°F (1010°C) UNITS			2200°F (1204°C) UNITS			W/O VESTIBULE	W/ VESTIBULE
INSIDE DIA	LENGTH	OD	MODEL NO	WATTS	VOLTS	MODEL NO	WATTS	VOLTS	IP-ID-L	VIP-ID-VID-VL
0.75	6	1.6875	RL101	110	28.5	RH201	145	28.5	IP-2.5-6	VIP-2.5-10-0.00-2
0.75	12	1.6875	RL102	215	57.5	RH202	285	57.5	IP-2.5-12	VIP-2.5-16-0.00-2
0.75	18	1.6875	RL103	325	115	RH203	425	115	IP-2.5-18	VIP-2.5-22-0.00-2
0.75	24	1.6875	RL104	425	115	RH204	570	115	IP-2.5-24	VIP-2.5-28-0.00-2
1	6	2.0625	RL106	145	57.5	RH206	190	57.5	IP-2.5-6	VIP-2.5-10-0.00-2
1	12	2.0625	RL107	285	115	RH207	380	115	IP-2.5-12	VIP-2.5-16-0.00-2
1	18	2.0625	RL108	425	115	RH208	570	115	IP-2.5-18	VIP-2.5-22-0.00-2
1	24	2.0625	RL109	570	115	RH209	760	115	IP-2.5-24	VIP-2.5-28-0.00-2
1	30	2.0625	RL110	1095	115	RH210	1275	230	IP-2.5-30	VIP-2.5-34-0.00-2
1.25	2	2.0625	RL111	80	28.5	RH211	100	28.5	IP-2.5-2	VIP-2.5-6-0.00-2
1.25	4	2.0625	RL112	160	57.5	RH212	200	57.5	IP-2.5-4	VIP-2.5-8-0.00-2
1.25	6	2.0625	RL113	225	57.5	RH213	290	57.5	IP-2.5-6	VIP-2.5-10-0.00-2
1.25	8	2.0625	RL114	300	115	RH214	365	115	IP-2.5-8	VIP-2.5-12-0.00-2
1.25	10	2.0625	RL115	375	115	RH215	425	115	IP-2.5-10	VIP-2.5-14-0.00-2
1.25	12	2.0625	RL116	420	115	RH216	600	115	IP-2.5-12	VIP-2.5-16-0.00-2
1.25	18	2.0625	RL117	600	115	RH217	725	115	IP-2.5-18	VIP-2.5-22-0.00-2
1.625	6	2.625	RL121	310	115	RH221	390	115	IP-4.5-6	VIP-4.5-10-0.00-2
1.625	12	2.625	RL122	610	115	RH222	720	115	IP-4.5-12	VIP-4.5-16-0.00-2
1.625	18	2.625	RL123	870	115	RH223	1010	230	IP-4.5-18	VIP-4.5-22-0.00-2
1.625	24	2.625	RL124	1210	230	RH224	1360	230	IP-4.5-24	VIP-4.5-28-0.00-2
1.625	30	2.625	RL125	1350	230	RH225	1420	230	IP-4.5-30	VIP-4.5-34-0.00-2
2	6	3.1875	RL131	350	57.5	RH231	425	57.5	IP-4.5-6	VIP-4.5-10-0.00-2
2	12	3.1875	RL132	650	115	RH232	825	115	IP-4.5-12	VIP-4.5-16-0.00-2
2	18	3.1875	RL133	1150	230	RH233	1375	230	IP-4.5-18	VIP-4.5-22-0.00-2
2	24	3.1875	RL134	1400	230	RH234	1650	230	IP-4.5-24	VIP-4.5-28-0.00-2
2	30	3.1875	RL135	1650	230	RH235	2025	230	IP-4.5-30	VIP-4.5-34-0.00-2
2.325	2.5	3.4375	RL141	200	57.5	RH241	250	57.5	IP-4.5-2.5	VIP-4.5-6.5-0.00-2
2.325	4	3.4375	RL142	300	57.5	RH242	360	57.5	IP-4.5-4	VIP-4.5-8-0.00-2
2.325	6	3.4375	RL143	450	115	RH243	520	115	IP-4.5-6	VIP-4.5-10-0.00-2
2.325	8	3.4375	RL144	600	115	RH244	615	115	IP-4.5-8	VIP-4.5-12-0.00-2
2.325	12	3.4375	RL145	880	115	RH245	950	230	IP-4.5-12	VIP-4.5-16-0.00-2
2.325	18	3.4375	RL146	1105	230	RH246	1295	230	IP-4.5-18	VIP-4.5-22-0.00-2
2.325	24	3.4375	RL147	1190	230	RH247	1460	230	IP-4.5-24	VIP-4.5-28-0.00-2
2.325	30	3.4375	RL148	1725	230	RH248	1960	230	IP-4.5-30	VIP-4.5-34-0.00-2
3	3	4.25	RL151	310	57.5	RH251	360	57.5	IP-4.5-3	VIP-4.5-7-0.00-2
3	6	4.25	RL152	585	115	RH252	620	115	IP-4.5-6	VIP-4.5-10-0.00-2
3	9	4.25	RL153	700	115	RH253	920	115	IP-4.5-9	VIP-4.5-13-0.00-2
3	12	4.25	RL154	835	115	RH254	1130	230	IP-4.5-12	VIP-4.5-16-0.00-2
3	15	4.25	RL155	1010	230	RH255	1640	230	IP-4.5-15	VIP-4.5-19-0.00-2
3	18	4.25	RL156	1275	230	RH256	1720	230	IP-4.5-18	VIP-4.5-22-0.00-2
3	24	4.25	RL157	1760	230	RH257	2280	230	IP-4.5-24	VIP-4.5-28-0.00-2
3	30	4.25	RL158	1910	230	RH258	2815	230	IP-4.5-30	VIP-4.5-34-0.00-2
3.75	6	5	RL161	720	115	RH261	825	115	IP-7.5-6	VIP-7.5-10-0.00-2
3.75	12	5	RL162	1180	230	RH262	1650	230	IP-7.5-12	VIP-7.5-16-0.00-2
3.75	18	5	RL163	1760	230	RH263	2230	230	IP-7.5-18	VIP-7.5-22-0.00-2
3.75	24	5	RL164	2060	230	RH264	3230	230	IP-7.5-24	VIP-7.5-28-0.00-2
3.75	30	5	RL165	2850	230	RH265	3850	230	IP-7.5-30	VIP-7.5-34-0.00-2
3.75	36	5	RL166	3290	230	RH266	4235	230	IP-7.5-36	VIP-7.5-40-0.00-2
4.125	6	5.75	RL167	750	115	RH267	850	115	IP-7.5-6	VIP-7.5-10-0.00-2
4.125	12	5.75	RL168	1200	230	RH268	1700	230	IP-7.5-12	VIP-7.5-16-0.00-2
4.125	18	5.75	RL169	1800	230	RH269	2250	230	IP-7.5-18	VIP-7.5-22-0.00-2
4.125	24	5.75	RL170	2100	230	RH270	3300	230	IP-7.5-24	VIP-7.5-28-0.00-2
5	3	6.75	RL171	435	115	RH271	590	115	IP-7.5-3	VIP-7.5-7-0.00-2
5	6	6.75	RL172	860	115	RH272	1060	230	IP-7.5-6	VIP-7.5-10-0.00-2
5	9	6.75	RL173	1200	230	RH273	1450	230	IP-7.5-9	VIP-7.5-13-0.00-2
5	12	6.75	RL174	1410	230	RH274	2010	230	IP-7.5-12	VIP-7.5-16-0.00-2
5	15	6.75	RL175	1710	230	RH275	2310	230	IP-7.5-15	VIP-7.5-19-0.00-2
5	18	6.75	RL176	2010	230	RH276	2510	230	IP-7.5-18	VIP-7.5-22-0.00-2
5	24	6.75	RL177	2770	230	RH277	3770	230	IP-7.5-24	VIP-7.5-28-0.00-2
5	30	6.75	RL178	3270	230	RH278	4270	230	IP-7.5-30	VIP-7.5-34-0.00-2
5.5	6	7.375	RL172A	890	115	RH272A	1125	230	IP-8.5-6	VIP-8.5-10-0.00-2
5.5	12	7.375	RL174A	1700	230	RH274A	2230	230	IP-8.5-12	VIP-8.5-16-0.00-2
5.5	18	7.375	RL176A	2535	230	RH276A	3400	230	IP-8.5-18	VIP-8.5-22-0.00-2
5.5	24	7.375	RL177A	3250	230	RH277A	4100	230	IP-8.5-24	VIP-8.5-28-0.00-2
6	6	7.625	RL181	900	230	RH281	1150	230	IP-8.5-6	VIP-8.5-10-0.00-2
6	12	7.625	RL182	1800	230	RH282	2300	230	IP-8.5-12	VIP-8.5-16-0.00-2
6	18	7.625	RL183	2700	230	RH283	3700	230	IP-8.5-18	VIP-8.5-22-0.00-2
6	24	7.625	RL184	3400	230	RH284	4200	230	IP-8.5-24	VIP-8.5-28-0.00-2
7	6	8.75	RL192	1010	230	RH292	1170	230	IP-9.5-6	VIP-9.5-10-0.00-2
7	12	8.75	RL193	1900	230	RH293	2300	230	IP-9.5-12	VIP-9.5-16-0.00-2
7	18	8.75	RL194	2820	230	RH294	3720	230	IP-9.5-18	VIP-9.5-22-0.00-2
7	24	8.75	RL195	3400	230	RH295	4800	230	IP-9.5-24	VIP-9.5-28-0.00-2
7	30	8.75	RL196	4300	230	RH296	5800	230	IP-9.5-30	VIP-9.5-34-0.00-2

RL AND RH QUARTER-SECTIONS									INSULATION PACKAGES 180° HALF -SECTION	
HEATER DIMENSIONS			1850°F (1010°C) UNITS			2200°F (1204°C) UNITS			°W/O VESTIBULE	W/ VESTIBULE
INSIDE DIA	LENGTH	OD	MODEL NO	WATTS	VOLTS	MODEL NO	WATTS	VOLTS	IP-ID-L	VIP-ID-VID-VL
8.25	8	9.75	RL1001	910	230	RH2001	1070	230	IP-10.5-8	VIP-10.5-12-0.00-2
8.25	16	9.75	RL1002	1640	230	RH2002	2140	230	IP-10.5-16	VIP-10.5-20-0.00-2
8.25	24	9.75	RL1003	2260	230	RH2003	3340	230	IP-10.5-24	VIP-10.5-28-0.00-2
10	6	11.75	RL1006	750	115	RH2006	1015	230	IP-12.5-6	VIP-12.5-10-0.00-2
10	12	11.75	RL1007	1500	230	RH2007	2010	230	IP-12.5-12	VIP-12.5-16-0.00-2
10	18	11.75	RL1008	2200	230	RH2008	2900	230	IP-12.5-18	VIP-12.5-22-0.00-2
10	24	11.75	RL1009	3100	230	RH2009	4020	230	IP-12.5-24	VIP-12.5-28-0.00-2
11.5	6	13.25	RL1101	875	115	RH2101	1050	230	IP-14-6	VIP-14-10-0.00-2
11.5	12	13.25	RL1102	1750	230	RH2102	2100	230	IP-14-12	VIP-14-16-0.00-2
11.5	18	13.25	RL1103	2625	230	RH2103	3150	230	IP-14-18	VIP-14-22-0.00-2
11.5	24	13.25	RL1104	3500	230	RH2104	4200	230	IP-14-24	VIP-14-28-0.00-2
12.125	6	13.875	RL1201	890	115	RH2201	1100	230	IP-14.5-6	VIP-14.5-10-0.00-2
12.125	12	13.875	RL1202	1780	230	RH2202	2200	230	IP-14.5-12	VIP-14.5-16-0.00-2
12.125	18	13.875	RL1203	2670	230	RH2203	3300	230	IP-14.5-18	VIP-14.5-22-0.00-2
12.125	24	13.875	RL1204	3560	230	RH2204	4400	230	IP-14.5-24	VIP-14.5-28-0.00-2

RL AND RH SIXTH-SECTIONS									INSULATION PACKAGES 180° HALF -SECTION	
HEATER DIMENSIONS			1850°F (1010°C) UNITS			2200°F (1204°C) UNITS			W/O VESTIBULE	W/ VESTIBULE
INSIDE DIA	LENGTH	OD	MODEL NO	WATTS	VOLTS	MODEL NO	WATTS	VOLTS	IP-ID-L	VIP-ID-VID-VL
15	6	16.75	RL1501	700	115	RH2501	860	115	IP-17.5-6	VIP-17.5-10-0.00-2
15	12	16.75	RL1502	1400	230	RH2502	1720	230	IP-17.5-12	VIP-17.5-16-0.00-2
15	18	16.75	RL1503	2100	230	RH2503	2580	230	IP-17.5-18	VIP-17.5-22-0.00-2
15	24	16.75	RL1504	2800	230	RH2504	3440	230	IP-17.5-24	VIP-17.5-28-0.00-2
15	30	16.75	RL1505	3500	230	RH2505	4300	230	IP-17.5-30	VIP-17.5-34-0.00-2
18.5	6	20.375	RL1801	970	115	RH2801	1200	230	IP-21-6	VIP-21-10-0.00-2
18.5	12	20.375	RL1802	1890	230	RH2802	1990	230	IP-21-12	VIP-21-16-0.00-2
18.5	18	20.375	RL1803	2750	230	RH2803	3400	230	IP-21-18	VIP-21-22-0.00-2
18.5	24	20.375	RL1804	3300	230	RH2804	3950	230	IP-21-24	VIP-21-28-0.00-2

RL AND RH EIGHTH-SECTIONS									INSULATION PACKAGES 180° HALF -SECTION	
HEATER DIMENSIONS			1850°F (1010°C) UNITS			2200°F (1204°C) UNITS			W/O VESTIBULE	W/ VESTIBULE
INSIDE DIA	LENGTH	OD	MODEL NO	WATTS	VOLTS	MODEL NO	WATTS	VOLTS	IP-ID-L	VIP-ID-VID-VL
22.5	6	24.5	RL8101	850	230	RH8201	1025	230	IP-25-6	VIP-25-10-0.00-2
22.5	12	24.5	RL8102	1700	230	RH8202	2100	230	IP-25-12	VIP-25-16-0.00-2
22.5	18	24.5	RL8103	2550	230	RH8203	3125	230	IP-25-18	VIP-25-22-0.00-2
22.5	24	24.5	RL8104	3400	230	RH8204	4150	230	IP-25-24	VIP-25-28-0.00-2

RL AND RH TWELFTH-SECTIONS								
HEATER DIMENSIONS			1850°F (1010°C) UNITS			2200°F (1204°C) UNITS		
INSIDE DIA	LENGTH	OD	MODEL NO	WATTS	VOLTS	MODEL NO	WATTS	VOLTS
39	6	42.5	RL3910	900	230	RH3920	1100	230
39	12	42.5	RL3911	1800	230	RH3921	2200	230
39	18	42.5	RL3912	2700	230	RH3922	3300	230
39	24	42.5	RL3913	3600	230	RH3923	4400	230
39	30	42.5	RL3914	4500	230	RH3924	5500	230