


# CRISTAN

## Cristallizator



#### Ingredients:

CRISTAN contains: less than 5% non-ionic surfactants. Other ingredients: magnesium hexafluorsilicate, glycols. pH-value: approx. 1

#### Performance:

CRISTAN gives more gloss to all calcareous stone floors which are sensitive to acids and make them scratch and abrasionproof, resistant to dirt and easy to clean. The co-lors of the natural stone floors regain their original gloss, clear appearance while simultaneously retaining the natural hardness of the surface. Floors treated with CRISTAN facilitate cleaning and continue to shine like new for a long time. High yield as a result of a minimum use of the product. No irritating odour during or after the application. If used properly, no pollution of waste water. Damages caused to natural stone floors for example through fruit juices, lemonade with caffein and similar products can be rectified with a minimum of effort or resp. recristallized without any noticible optical difference to the remainder of the floor.

#### **Application notes:**

For use on all calcareous stone floors which are sensitive to acid, such as marble, travertine, terrazzo and other concrete stones. Do not use on ceramic floors, granite, sandstone or slate.

#### Usage:


Remove any dirty or sticky residues on the floor with a stripper (LINAX or QUICK-STRIPPER). Leave to dry.

With the spray head closed, shake the bottle of CRISTAN thoroughly before use. Spray CRISTAN undiluted in a fine mist over the floor and <u>immediately</u> work in using a slow face steel wool mat or steel wool strips until the floor shines.

ArtNr.: 04641	200 I
ArtNr.: 04741	10 l can

TANA-CHEMIE GMBH • Ingelheimstr. 1-3 • 55120 Mainz

Tel.: +49-6131-964-03 • Fax: +49-6131-964-2414 • www.tana.de



Carry out on areas of approx. 1m<sup>2</sup> at a time. Turn or replace the steel wool in due time. <u>Do not use rusty steel wool.</u> The ideal combination is achieved with a coarse steel wool and following this up with a subsequent treatment-also with CRISTAN-and a fine steel wool. The surface processed should be polished with a clean, fine steel wool or polishing pad.

<u>Important:</u> CRISTAN has extremely high yielding proper-ties. In the case of medium roughness of the surface of the natural stone floor, average use is about 12-15ml per m<sup>2</sup>. Apply only as a fine mist (approximately 2 trigger pump motions per m<sup>2</sup>).

#### Precautions for use:

Harmful. Contains magnesium hexafluorsilicate. Harmful if swallowed. Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Avoid contact with skin and eyes. Do not inhale spray. Only use on calcareous stone floors; avoid other materials. Acid-sensitive materials of fittings should be covered or removed (using adhesive taps).

### Ecology:

This product is subject to regulations governing the environmental compatibility of washing and cleaning agents and the associated regulations on the biological degradability of the raw materials used.

Comprehensive information on the environmental characteristics of this product is available on request.

Give only completely emptied packaging to special waste disposer.

This product is designated for industrial use.



WERNER & MERTZ PROFESSIONAL VERTRIEBS GMBH • Neualmerstr. 11-13 • 5400 Hallein • Tel.: +43-6245-87486 • Fax: +43-6345-87286-707 • www.tana.at