GUMAKOL – GKM - 86

GUMAKOL-GKM -86 is a liquid against frozening and depositing of ice on pneumatic connections and devices,conveyor belts, elevators in external conditions at low temperatures.At the same time performs also melting of already dep-Osited ice on them and doesn't cause damage to the same time is cleaning them.

Usage

GUMAKOL-GKM-86 Iis used with greasing on the surfaces with brush or applying it with spraying pump.

Note

-To store it in a dry dark place with ventilating conditions.
-To keep it away from fireing sources.
-If it came to an eye contact,flash it at once with planty of wather and to ask for a medical service.
-To use protective equipment during usage .
-Storage:From -40 C to +35 C.
-Not to dispose it on high sun light.
-Self live:2 years.

CHEMICAL-PHYSICAL CHARACTERISTICS

1.1 Apperance	light green colour
1.2 Content of primaty alchocols	<88
1.3 Freezing point	under -45 C
1.4 Boiling point	80 C
1.5 Breaking index	1.360
1.6 Content of high alcohols	>0.5
1.7 Corrosivity	corrosively negative

2.1 Content of esters scaling on ethyl acetate in mgl/1000	37
2.2 Content of aldehydes calculated in acetaldehyde in volume of product.	0.001
2.3 Content of eteric oils	0
2.4 Content of methanol	0
2.5 Content of fufurol	0

PACKING AND STORAGE

GUMAKOL-GKM-86 is packed in plastic drums of 50-220 L.Storage in closed rooms is reco Electrolux-Bitola