

T-PL1 Plastic Body Solenoid Valve

Plastic Body Solenoid Valve, Dry Type Valve

TORK, T-PL1 Series normally closed

- Application : acid, water, chemical proses, automation system, machines
- Coil Voltage : 230, 220V, 110V, 24V, 12V AC, 24V, 12V DC
- Protection Class : IP 65 with plug
- Seal : VITON
- Way : 2/2 way
- Position : N.C
- Tube Internal Part : stainless steel

Size	Product Type	Orifice (mm)	Kv (lt/min)	Pressure (bar)		Temp. (°C)		Body	Seal
				Min	Max	Min	Max		
G	T-PL1 Series							plastic	---
1/4"	T-PL1.101	4,5	5	0.....1		-10.....90		plastic	VITON
3/8"	T-PL1.102	8	16	0,5.....10		-10.....80		plastic	VITON
1/2"	T-PL1.103	12	36	0,5.....10		-10.....80		plastic	VITON

T-PL2 Series Plastic Body Solenoid Valves, Normally Closed



Product code : T-PL2.104
 Brand : TORK

T-PL2 Series Plastic Body Solenoid Valves, Normally Closed

TORK Plastic Body Solenoid Valves

T-PL2 Series normally closed



Application : water, hot water washing machines, irrigaton, cooling water sytem in machines
 Voltage : 230, 220V,,,on request 24V AC, 24V DC
 Protection Class : one coil, IP65
 Seal : NBR
 Way : 2/2 way N.C

Size	Product Type	Orifice (mm)	Kv (lt/min)	Pressure(bar)		Temp. (°C)		Body	Seal	Net Weight (kg)
				Min	Max	Min	Max			
3/4"	T-PL2.102	10	26	0,3.....10		-10.....140		plastic	EPDM	0,10
3/4"	T-PLM2.102	10	26	0,3.....10		-10.....140		plastic	EPDM	0,10
3/4"	T-PLN2.102	10	26	0,3.....10		-10.....140		plastic	EPDM	0,10

on request: 2 coils, 3 coils.