





Selection Guide for Heraeus Deuterium Lamps



Heraeus' broad range of deuterium lamps fulfils all of the needs of instrument manufacturers: standard or extended lifetime, quartz glass or UV glass envelopes, optional see-through versions and many specialist lamps e.g. for very short wavelengths (vacuum UV) or boosted output.

Our selection guide helps you to find the right deuterium lamp in terms of materials, geometry and operating parameters.





High Stability Deuterium Lamps – Lifetime 2000 hours*

Heraeus long-life deuterium lamps combine a guaranteed lifetime of 2000 hours with unmatched stability of the output over the entire life. This sets them apart from many other long-life lamps on the market and makes them the ideal choice for high-end HPLC instruments.

Lamp Code	Window Material	Spectral Range (nm)	Aperture Diameter (mm)	Strike Voltage (V)	Anode Current (mA dc)	Anode Voltage (V)	Output Stability		Filament Rating				Part Number
							Noise % p-p	Drift %/h	Warm-up		Operation		
									V dc	A dc	V dc	A dc	
DX 202 R	Fused silica	185-400	1.0	350	300	80	0.005	± 0.5	2.5	5.8	0	0	80001131
DX 201/05 RJ	Fused silica	185-400	0.5	350	300	80	0.005	± 0.5	2.5	5.8	0	0	80008685
DX 223	Fused silica	185-400	1.0	350	300	80	0.005	± 0.5	2.5	4	0	0	80006631
DX 226/05	Fused silica	185-400	0.5	350	300	80	0.005	± 0.5	2.5	4	0	0	80033068
DX 227/05 J	Fused silica	185-400	0.5	350	300	80	0.005	± 0.5	2.5	4	0	0	80035276
PR 41069	UV Glass	190-400	0.5	400	300	80	0.005	± 0.5	10	0.9	6	0.5	80051960
DX 246	Fused silica	185-400	1.0	350	300	80	0.005	± 0.5	10-12	0.8-1.0	3-6	0.3-0.45	80006934
DX 246/05 J	Fused silica	185-400	0.5	350	300	80	0.005	± 0.5	10-12	0.8-1.0	3-6	0.3-0.45	80013440

* The guaranteed lifetime is defined as the time in which the radiant power of the lamp has dropped to 50% of its initial value measured at 230nm and 300mA operating current.

High Intensity Lamps - Lifetime 1000 hours*

Heraeus high intensity deuterium lamps with the new “Enhanced Lifetime Performance” (ELP) technology maintain twice the residual intensity compared to standard D2 lamps at the end of life. It provides a particular advantage in the deep UV region between 160 to 230nm for all Heraeus D2 lamps with synthetic quartz window.

Lamp Code	Window Material	Spectral Range (nm)	Aperture Diameter (mm)	Strike Voltage (V)	Anode Current (mA dc)	Anode Voltage (V)	Output Stability		Filament Rating				Part Number
							Noise % p-p	Drift %/h	Warm-up		Operation		
									V dc	A dc	V dc	A dc	
DO 605 T	Synthetic Silica	160-400	1.0	350	300	75	0.05	± 0.5	2	5.8	0	0	80052430
Do 605 TJ	Synthetic Silica	160-400	1.0	350	300	75	0.05	± 0.5	2	5.8	0	0	80052431
DO 660/05 J	Synthetic Silica	160-400	0.5	350	300	85	0.05	± 0.5	2	5.8	0	0	45002349
DO 650 J	Synthetic Silica	160-400	1.0	350	300	80	0.05	± 0.5	10-12	0.9	3-6	0.3-0.45	80051718
DO 655 J	Synthetic Silica	160-400	1.0	350	300	75	0.05	± 0.5	10-12	0.9	3-6	0.3-0.45	80002154
R07	Synthetic Silica	160-400	1.0	350	300	80	0.05	± 0.5	10	1.0	7	0.7	80013769
R47	Synthetic Silica	160-400	0.5	350	300	75	0.05	± 0.5	10	1.5	7	1	80013793

* The guaranteed lifetime is defined as the time in which the radiant power of the lamp has dropped to 50% of its initial value measured at 230nm and 300mA operating current.

See-Through Deuterium Lamp Types*

The see-through type lamp offers a straight-line arrangement of a tungsten halogen lamp, deuterium lamp and optical system.

Lamp Code	Window Material	Spectral Range (nm)	Aperture Diameter (mm)	Strike Voltage (V)	Anode Current (mA dc)	Anode Voltage (V)	Output Stability		Filament Rating				Life* (h)	Part Number
							% p-p	% /h	Warm-up		Operation			
									V dc	A dc	V dc	A dc		
DO 660/05 J	Synthetic Silica	160-400	0.5	350	300	85	0.05	± 0.5	2	5.8	0	0	1500	45002349
DS 270 J	Fused silica	185-400	1.0	350	300	85	0.005	± 0.5	2.5	4	0	0	1000	80000707
DS 270/05	Fused silica	185-400	0.5	350	300	85	0.005	± 0.5	2.5	4	0	0	1000	45006036
DS 270/05 J	Fused silica	185-400	0.5	350	300	85	0.005	± 0.5	2.5	4	0	0	1000	80006982
DX 277/05 J	Fused silica	185-400	0.5	350	300	85	0.005	± 0.5	2.5	4	0	0	2000	80013311
PR 41016	UV Glass	190-400	0.5	400	300	80	0.005	± 0.5	3.0	3	1	1	2000	80051984
DX 282/05 TJ	Fused silica	185-400	0.5	350	300	80	0.005	± 0.5	10-12	0.8-1.0	3-6	0.3-0.45	2000	80009851
DO 680 J	Synthetic Silica	160-400	1.0	350	300	80	0.05	± 0.5	10-12	0.8-1.0	3-6	0.3-0.45	1500	80036302

* The guaranteed lifetime is defined as the time in which the radiant power of the lamp has dropped to 50% of its initial value measured at 230nm and 300mA operating current.

VUV Lamps – 30 Watt – Lifetime 500 hours*

Vacuum UV (VUV) lamps are deuterium lamps that are especially designed to supply deep UV light down to a wavelength of 115 nm.

Lamp Code	Window Material	Spectral Range (nm)	Aperture Diameter (mm)	Strike Voltage (V)	Anode Current (mA dc)	Anode Voltage (V)	Output Stability		Filament Rating				Part Number
							% p-p	% /h	Warm-up		Operation		
									V dc	A dc	V dc	A dc	
V01	MgF2	115-400	1.0	350	300	70	0.2	± 0.5	10	1.0	0	0	80017697
V02	Synthetic Silica	160-400	1.0	350	300	70	0.2	± 0.5	10	1.0	0	0	80017698
V03	MgF2	115-400	1.0	350	300	70	0.2	± 0.5	10	1.0	0	0	80017699
V04	Synthetic Silica	160-400	1.0	350	300	70	0.2	± 0.5	10	1.0	0	0	80017700
V05	MgF2	115-400	1.0	350	300	70	0.2	± 0.5	10	1.0	0	0	80020174
F03	Synthetic Silica	160-400	1.0	280	300	65	0.05	± 2.28	10	1.5	7	1.0	80013064
F05	MgF2	115-400	1.0	300	300	65	0.05	± 2.28	10	1.5	7	1.0	80017478
J59	MgF2	115-400	1.0	300	300	80	0.005	± 0.01	10	1.5	7	1.0	80017520

* The guaranteed lifetime is defined as the time in which the radiant power of the lamp has dropped to 50% of its initial value measured at 230nm and 300mA operating current.

Water-cooled Deuterium Lamps – 200 Watt – Lifetime 1000 hours*

Heraeus is specialized on high power VUV lamps with up to 200 W. The D200 lamps come equipped complete with a cooling jacket for easy installation in water cooled operations

Lamp Code	Window Material	Spectral Range (nm)	Aperture Diameter (mm)	Strike Voltage (V)	Anode Current (A DC)	Anode Voltage (V)	Output Stability		Filament Rating				Part Number
							% p-p	% /h	Warm-up		Operation		
									V dc	A dc	V dc	A dc	
D 200 F	Synthetic Silica	160-400	1.0	500	0.9 to 1.8	110	0.05	± 0.5	6	4.5	3	2.5	56001671
D 200 F-HV	Synthetic Silica	160-400	1.0	500	0.9 to 1.8	110	0.05	± 0.5	6	4.5	3	2.5	45006278
D 200 VUV	MgF2	115-400	1.0	500	0.9 to 1.8	110	0.05	± 0.5	6	4.5	3	2.5	45006010

** The guaranteed lifetime is defined as the time in which the radiant power of the lamp has dropped to 50% of its initial value measured at 250nm and 0.9A operating current.

Examples of prealigned Replacement Deuterium Lamps



To find the right lamp for your instrument, please use our online Lamp Finder at www.heraeus-noblelight.com/analytics. Heraeus deuterium lamps are available in precisely pre-aligned versions as replacement lamps for almost all suitable instruments. You will also find a comprehensive list of approved replacement lamp distributors at our website.

Germany

Heraeus Noblelight GmbH
Heraeusstraße 12-14
63450 Hanau
Phone +49 6181 35-5085
hng-analyticallamps@heraeus.com
www.heraeus-noblelight.de

U.S.A.

Heraeus Noblelight LLC
2150 Northmont Parkway
Duluth, GA 30096
Phone +1 770 418 0707
analytics-usa@heraeus.com
www.heraeus-noblelight.com

United Kingdom

Heraeus Noblelight Analytics Ltd.
Nuffield Close
Cambridge CB4 1SS
Phone +44 1223 424100
hna-analytics@heraeus.com
www.heraeus-noblelight.com

PR China

Heraeus (Shenyang) Noblelight Ltd.
4F, 11th Building, No.99 Tianzhou Rd.
Shanghai, 200233
Phone +86 21 5445-2255
info.hns@heraeus.com
www.heraeus-noblelight.cn

France

Heraeus Noblelight France
12, av. du Québec - Bât I 2
91945 Courtaboeuf Cedex
Phone +33 1 69184848
philippe.wuattier@heraeus.com
www.heraeus-noblelight.com

Australia

Heraeus Amba Australia Pty. Ltd.
Unit 3, 41-49 Norcal Road
NUNAWADING, VICTORIA 3131
Phone +61 3 9874 7455
sales@heraeus-amba.com.au
www.heraeus-noblelight.com