

Thermo Speed Edition

2012

Express Catalogue for

UTECO



Special cables department

UTECO

www.uteco.mk

Special Cables



Express catalogue special cables 2012

2

Dear Customers,

2

You will find below a standardized list of special cables from us, which are always in stock at our warehouse, capable of solving the immediate need of the most demanding applications.

The catalogue includes code, type, basic technical description and a photo for visual recognition of our product.

This is a indicative list. Cables with different numbers of cores or pairs, different sections (mm²), insulation or color codes (standard), etc. are also available.

If your requests are not covered by this list, please contact us.

Content

Instrumentation & Bus Cables.....	3
Data & Control Cables.....	4
Compensating & extension cables	5
High Temperature Cables	6
International Color Code for Compensating & Extension Cables.....	7
Other catalogues.....	8
Ordering Form	9

Express catalogue special cables 2012

Instrumentation & Bus Cables

Code: 1-52-50-01-00-5
Type: RE-2Y(St)Y-fl 300 V 2x2x1,0 mm² Black
Insulation: PVC/OS/PVC
Resistance to temperature: up to 70°C
External diameter: 8,2 mm



Code: 1-52-50-02-00-9
Type: RE-Y(St)YSWAY-fl 300V 2X2X1,0 mm² Grey
Insulation: PVC/OS/PVC/SWA/PVC
Resistance to temperature: up to 70°C
External diameter: 15,00 mm



Code: 1-52-50-06-01-1
Type: RE-Yw(St)YwSWAYw-fl 300V 1X2X1,5 mm²
Insulation: PVC/OS/PVC/SWA/PVC
Resistance to temperature: up to 105°C
External diameter: 12,4 mm



Code: 1-51-50-02-00-0
Type: RE-2Y(ST)Y-PIMF 2x2x0,5 mm² Blue
Insulation: PVC/OS/IS/PVC
Resistance to temperature: up to 70°C
External diameter: 11,2 mm



Code: 1-51-50-08-02-6
Type: RE-2G(St)HSWAY-fl CI 500V 5x2x0,75 mm²
Insulation: Silicon Rubber/OS/LSZH/SWA/PVC
Resistance to temperature: up to 90°C
External diameter: 18,1 mm
Standard: IEC 60331 Fire Resisting (CI)



Code: 1-51-50-06-00-0
Type: PROFIBUS FMS/DP 1x2xAWG 22/1
Conductor: solid conductors
Resistance to temperature: up to 70°C
External diameter: 7,9 mm



Code: 1-00-50-06-00-1
Type: Profibus L2 7-wire 1x2x0,64
Conductor: 7 strand
Resistance to temperature: up to 70°C
External diameter: 7,3 mm



Code: 1-98-50-21-00-9
Type: CC-LINK BU 3x0,5 (AWG20/7)
Conductor: 7 strand
Resistance to temperature: up to 70°C
External diameter: 7,9 mm



Express catalogue special cables 2012

Data & Control Cables

Code: 1-50-50-09-51-0
Type: OZ-J 4X1,5 mm²
Insulation: PVC - PVC
Resistance to temperature: up to 70°C
External diameter: 7,1 mm



Code: 1-50-50-15-98-4
Type: LIYCY 7X1,0 mm²
Insulation: PVC – Braid - PVC
Resistance to temperature: up to 70°C
External diameter: 7,9 mm



Code: 1-50-50-13-15-0
Type: OZCuY-J 7X1,0 mm²
Insulation: PVC – PVC - Braid - PVC
Resistance to temperature: up to 70°C
External diameter : 11,6mm



Code: 1-50-50-17-09-0
Type: NYMH11YO-J (YPUR) 3X1,5 mm²
Insulation : Polyurethane - Polyurethane
Resistance to temperature: up to 70°C
External diameter: 7,9 mm
Very good chemical resistance



Code: 1-50-50-18-12-0
Type: S 200 3x0,75
Insulation: TPE-E - PUR
Resistance to temperature: up to 70°C
External diameter: 7,9 mm
Very good chemical resistance
Highly flexible for continues bending motions



Code: 1-50-50-22-05-0
Type: S 90 C 4x1,5 mm²
Insulation: PVC - braid - PUR
Resistance to temperature: up to 70°C
External diameter: 11,8 mm
Very good chemical resistance
Highly flexible for continues bending motions + braid



Code: 1-50-50-22-01-0
Type: ZKBi 1,0 mm² Y.T. 20 KV
Insulation: Silicone – Fiber glass- Silicone
Resistance to temperature: up to 180°C
External diameter: 8,0 mm
20 KV High Voltage cable



Express catalogue special cables 2012

Compensating & extension cables

Code: 1-50-50-23-01-0

Type: AN 11 LR 2X1,5 mm²

For thermocouple : Type K NiCr-Ni

Color code: Acc to IEC 584

Insulation: Silicone – Fiberglass-Braid

Resistance to temperature: up to 180°C

External diameter: 6,2 mm



5

Code: 1-50-50-23-02-0

Type: AN 11-4LR 4x1,50

For thermocouple: Type K NiCr-Ni

Color code: Acc to IEC 584

Insulation: Silicone – Silicone - Braid

Resistance to temperature: up to 180°C

External diameter: 9,3 mm



Code: 1-00-50-23-03-4

Type: 2X1,3 mm² PVC-PVC (flat)

For thermocouple: Type K NiCr-Ni

Color code: Acc to DIN 43710

Insulation : PVC - PVC

Resistance to temperature : up to 70°C

External diameter : 6,7 mm



Code: 1-00-50-23-08-0

Type: 2X0,22 mm PVC-PVC (Round)

For thermocouple: Type K NiCr-Ni

Color code: Acc to IEC 584

Insulation: PVC - PVC

Resistance to temperature: up to 70°C

External diameter: 4,0 mm



Code: 1-00-50-25-01-0

Type: JX 2X0,5 Fiber-Fiber-Braid

For thermocouple: Type J Fe-CuNi

Color code: Acc to IEC 584

Insulation: Fiber – Fiber - Braid

Resistance to temperature: up to 400°C

External diameter: 4,0 mm



Code: 1-83-50-23-09-0

Type: G/G-24-KK (G3 NICR-NI) 2x0,5

For thermocouple: Type K NiCr-Ni

Color code: Acc to ANSI MC 96.1

Insulation: Fiber - Fiber

Resistance to temperature: up to 400°C

External diameter: 2,0 mm



Code: 1-00-50-03-04-6

Type: RT-Y(St)YSWAY-fl 1x2x1,29 mm NiCr-Ni

For thermocouple: Type K NiCr-Ni

Color code: Acc to ANSI MC 96.1

Insulation: PVC–Aluminum foil -Steel Wire Armor-PVC

Resistance to temperature : up to 70°C

External diameter: 13,1mm



Code: 1-00-50-24-04-0

Type: SX PVC-SCH-PVC 16x2x0,50 mm²

For thermocouple: Type S PtRh10-Pt

Color code: Acc to DIN 43710

Insulation: PVC – Aluminum foil - PVC

Resistance to temperature : up to 70°C

External diameter : 19,2 mm



Express catalogue special cables 2012

High Temperature Cables

6

Code: 1-52-50-02-13-1
Type: SIHF-GLS(GLP) 3X1,5 mm²
Insulation: Silicone-Silicone-Fiberglassç-Braid
Resistance to temperature: up to 180°C
External diameter: 8,9 mm
Form: Round



6

Code: 1-00-50-02-13-0
Type: PFA-SS-PFA 3X1,5 mm²
Insulation: Teflon-Braid-Teflon
Resistance to temperature: up to 260°C
External diameter: 6,0 mm
Form: Round



Code: 1-98-50-02-13-7
Type: Teflon- Fiber-Braid 3XAWG16
Insulation: Teflon- Fiberglass-Braid
Resistance to temperature: up to 260°C
External diameter: 5,0 mm
Form: Round



Code: 1-00-50-00-00-0
Type: VIBRA RV 1.00 STV02 2X1,0 mm
Insulation: Vibraflame – Braid- Vibraflame
Resistance to temperature: -196°C ...+1565°C
External diameter: 7,0 mm
Form: Round



Code: 1-00-50-00-00-5
Type: PT100 3X0,5 FIBER-FIBER-BRAID
Insulation: Fiber – Fiber - Braid
Resistance to temperature: up to 400°C
External diameter: 3,0 mm
Form: Round



Code: 1-00-50-02-14-1
Type: Hyflon-Silicon 4X0,22 mm²
Insulation: Hyflon - Silicone
Resistance to temperature: up to 180°C
External diameter: 4,3 mm
Form: Round



Code: 1-20-50-00-00-4
Type: 62849 4X0,14mm²
Insulation: Teflon – Braid - Teflon
Resistance to temperature : up to 260°C
External diameter: 3,5 mm
Form: Round











































Special Cables



Express catalogue special cables 2012

International Color Code for Compensating & Extension Cables

					
	ANSI	DIN	IEC/CEI	BS	NF
JX					
KX					
TX					
NX					
EX					
WX					
VX					
SX/RX					

Special Cables



Express catalogue special cables 2012

Ordering Form

Please print this form out and send it to +30 211 1206 999

Company Name	
---------------------	--

Contact Name	
---------------------	--

Company Address	
------------------------	--

City	
-------------	--

Area	
-------------	--

Country	
----------------	--

Company Phone	
----------------------	--

Company Fax	
--------------------	--

Product Code	Length	Other Characteristics
---------------------	---------------	------------------------------

--	--	--

--	--	--

--	--	--

--	--	--

Signature