# Image: Constraint of the second state of the second st

### 2700 SERIES FUNCTIONAL FEATURES



A seat and writing table unit specially designed for use in schools, colleges and universities. Most commonly arranged in short rows, these modular elements are individually anchored to the floor and joined together by the worktop, which always has a continuous surface.

Each module comprises a rigid metal structure that supports the seat hinge, the backrest and the desk for the row behind.



Ovoj citez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva ,umnozuva niti kopira bez soglasnost od Elictroluks

vo sprotivno se snosat posledici vo smislana clenovite 163 i 164 od krivicniot zakon R.M. (povreda na avtorsko pravo)

5

5

5



This structure is adapted to the floor or tier profile so that the height of the seats and the writing desk relative to the floor is constant.

Both seat and backrest are made of 13 mm-thick moulded plywood with a beech wood veneer. Finished with two coats of two-component polyurethane varnish, sanded and polished between applications. Can also be dyed to suit the customer's colour requirements.

The seat has an automatic tip-up system in which a cast aluminium seat support pivots on the central structure. The return mechanism has a torsion spring - tested to 150,000 cycles without signs of fatigue – and self-lubricating roller bushings. It is silent and requires no maintenance.

The central support structure is made of oval tubing finished in electrostatic powder polyester paint and shielded seam arc welds. The structure is anchored to the floor by expansion plugs. The desk is made of hardboard finished in Formica and rounded, solid beech borders.

The document shelf consists of metal rod mesh painted in the same way as the other metal parts.

Adresa: ul.Braka Mingovi 18, 7000 Bitola; tel: 047/203-330 ,203 900ul.A.Guslarot.1a 02/329 8 130 Skopje

www.electrolux.com.mk www.elektroluks.com.mk e-mail: elek-palenzo@mt.net.mk



### **TECNICHAL CHARACTERISTICS**







Elektroluks is registered trademark of Elektrouks companies in Macedonia and other countries

### STRUCTURE:

Steel plate and tube, welded with continuous arc.

# PAINT:

Ovoj citez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva ,umnozuva niti kopira bez soglasnost od Elictroluks

vo sprotivno se snosat posledici vo smislana clenovite 1,63 i 1,64 od krivicniot zakon R.M. (povreda na avtorsko pravo)

5

5

Electrostatic powder expoy Coating thickness: 70-80 micra Grid adherence: 100%

# WOOD:

In beech wood curved by high-pressure steam, finished in two polyurethane varnished components

# FIRE STANDARS

England:	BS5852. Section 5. Ignition Sources 0, 1 and 5
Germany:	DIN54342 part 1 and 2
Italy:	CSE RF/4/83 classe 1. IM
Spain/France:	UNE 23727/NF 92-503
•	Upholstery: M1 / Foam: M4 / Plastic M3

# WEIGHT: 25 Kg.

VOLUME: 0,17 m<sup>3</sup> (K.D)

Adresa: ul.Braka Mingovi 18, 7000 Bitola; tel: 047/203-330 ,203 900ul.A.Guslarot.1a 02/329 8 130 Skopje

www.electrolux.com.mk www.elektroluks.com.mk e-mail: elek-palenzo@mt.net.mk