



Electrolux Bitola



Ovoj crtez e sopstvenost na Electrolux-Bitola.Bez negovo pismeno odobruvanje isti ot nesmee da se prepisuva ,umnozuvu nihi kopira bez soglasnost od Electroluks vo sprotno se snosat posledici vo smislana clenovite 163 i 164 od kivicniot zakon R.M. (povreda na avtorsko pravo)

Adresa: ul. Braќa Minѓovi br.18, Stipara Caršija Bišola
Adresa: ul. Ajosijol Guešarov 1-a G. T. C. Bунјаковец Skojje
Tel/Faks: 047/203-900; 203-330; 070/237-108
Tel/Faks: 02/329 8 130; 070/237 198
www.elektroluks.com.mk , electrolux@mt.net.mk

Elektroluks is registered trademark of Elektroluks companies in Macedonia and other countries



Electrolux Bitola

Ovo je crtez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje isiot nesmee da se prepisiva , umozuva nihi kopira bez soglasnost od Electroluks vo sprotnivo se snosat posledici vo smislana clenovite 163 i 164 od kivicionat zakon R.M. (povreda na avtorsko pravo)

MAGNETNI VENTILI ZA VODU I DRUGE NEUTRALNE TEČNOSTI SOLENOID VALVES FOR WATER AND OTHER INERT LIQUIDS



Dvoputni, bez napona zatvoreni, membranski od G1/2 do G2.
Two way normally closed, diaphragm operated, from G1/2 to G2.



Dvoputni, bez napona otvoreni, membranski od G1/2 do G2.
Two way normally open, diaphragm operated, from G1/2 to G2.



Dvoputni, membranski, bez napona zatvoreni, membranski za pritiske oko 0, od G1/2 do G2.
Two way normally closed, diaphragm operated, for very low pressures, from G1/2 to G2.



Dvoputni, bez napona zatvoreni, direktni od G1/8 do G1/2.
Two way normally closed, direct acting, from G1/8 to G1/2.

MAGNETNI VENTILI ZA VAZDUH I DRUGE GASOVITE MEDIJE SOLENOID VALVES FOR AIR AND OTHER GASEOUS FLUIDS



Troputni, direktni G1/8 i G1/4.
Three way, direct acting, G1/8 and G1/4.



Dvoputni, bez napona zatvoreni, direktni, G1/8 i G1/4.
Two way normally closed, direct acting, G1/8 and G1/4.



Dvoputni, bez napona zatvoreni, membranski ventili za pritiske blizu 0, od G1/2 do G2.
Two way normally closed, diaphragm-operated valves for very low pressures, from G1/2 to G2.



Dvoputni, bez napona zatvoreni, membranski, od G1/2 do G2.
Two way normally closed, diaphragm operated, from G1/2 to G2.



Dvoputni, za etprašivanje filtera, od G3/4 do G6/4.
Pulse valves for dust collector systems, G3/4 to G6/4

MAGNETNI VENTILI ZA PARU I VEOMA VRUČU VODU SOLENOID VALVES FOR STEAM AND VERY HOT WATER



Dvoputni, bez napona zatvoreni, membranski G1/2 i G1.
Two way normally closed, diaphragm operated, G1/2 to G1.



Dvoputni, bez napona zatvoreni, direktni sa regulacijom protoka G1/4.
Two way normally closed, direct acting, with flow regulation, G1/4.



Dvoputni bez napona zatvoreni, membranski, za pritiske oko 0, od G1/2 do G2.
Two way normally closed, diaphragm operated, for very low pressures, from G1/2 to G2.



Dvoputni, bez napona zatvoreni, direktni, G1/2.
Two way normally closed, direct acting, G1/2.

PLASTIČNI MAGNETNI VENTILI PLASTIC SOLENOID VALVES



Dvoputni, bez napona zatvoreni, sa pregradnom membranom za agresivne tečnosti, G1/2.
Two way normally closed, with separating diaphragm for aggressive liquids G1/2.



Dvoputni, bez napona zatvoreni, membranski, spoljni navoj G3/4.
Two way normally closed, diaphragm operated, male thread connections G3/4.



Dvoputni, bez napona zatvoreni, membranski, priključci M12x1 i G3/4 spoljni navoj.
Two way normally closed, diaphragm operated, male thread connections M12x1 and G3/4.



Troputni, bez napona zatvoreni, membranski, ulaz: spoljni navoj G3/4, izlaz: cijevni nastavak \varnothing 10.
Three way normally closed, diaphragm operated, inlet: male thread G3/4, outlet: hose connection \varnothing 10.

MAGNETNI VENTILI ZA RAZNE NAMENE SOLENOID VALVES FOR DIFFERENT PURPOSES



Ex izvedba, dvoputni bez napona zatvoreni, membranski, od G1/2 do G2.
Explosion proof two way normally closed, diaphragm operated, from G1/2 to G2.



Dvoputni, sigurnostni za plin, od G1/2 do G2.
Two way safety valve for gas, from G1/2 to G2.



Dvoputni, bez napona zatvoreni, za rashladne medije, SAE 1/4" i SAE 3/8".
Two way normally closed for refrigerants, SAE 1/4" and SAE 3/8".



Kilpni, sa servo delovanjem, za visoke pritiske - do 120 bar.
Pilot operated piston valves for high pressures - up to 120 bar, G1/2.



Kilpni, upravljani drugim medijem, za pritiske do 16 bar i temperature do 180°C, od G1/2 do G2.
External pilot operated piston valves for pressures up to 16 bar and fluid temperatures up to 180°C, G1/2 to G2.

MAGNETNI VENTILI ZA POSEBNE NAMENE SOLENOID VALVES FOR SPECIAL PURPOSES



Naša posebnost: na zahtev kupca - posebne izvedbe.
Our speciality: special versions to meet specific customers' request.



JAKŠA
MAGNETNI VENTILI

Adresa: ul. Braća Minčovi br.18, Stijara Caršija Bitola
Adresa: ul. Ajosijol Guslarov 1-a G. T. C. Bunjakovec Skopje
Tel/Faks: 047/203-900; 203-330; 070/237-108
Tel/Faks: 02/329 8 130; 070/237 198
www.elektroluks.com.mk , electrolux@mt.net.mk

Electroluks is registered trademark of Elektroluks companies in Macedonia and other countries