



Електролукс Electrolux Bitola

Elektricni grejaci za potopuvanje za kiseli rastvori Heating Equipment

A-H Palenzo 316 Stainless Steel Heaters

A-D Heaters with Dial Temperature Controller have a sensitivity of $\pm 1^\circ\text{F}$ when liquid is stirred. Top-mounted pilot light indicates that heater is on. Choose from four styles "A" loop, "B" short rod, "C" flat, and "D" long rod (not pictured), which is the same style as "B" only longer. Heaters feature a plastic grip handle and a 6-ft. three-wire cord; 115 VAC models also include a plug.

E Heaters with Thermostatic Temperature Controller have a sensitivity of $\pm 2^\circ\text{F}$ ($\pm 1^\circ\text{C}$) in an agitated bath. Heaters feature a coiled heating element to concentrate heat at bottom of vessel. A 6-ft. three-wire cord with plug is included. Voltage transformer (listed below) is required for 230 VAC operation.

A-01578-08 Voltage transformer; 230 VAC, 50/60 Hz. Use with 03052-10 and -30 heaters. Shpg wt 15 lb (6.8 kg)

A-01578-09 Voltage transformer; 230 VAC, 50/60 Hz. Use with 03052-20, -40, and -50 heaters. Shpg wt 20 lb (9.1 kg)

F-H Heaters with Dial Temperature Controller have a sensitivity of $\pm 1^\circ\text{F}$ ($\pm 0.6^\circ\text{C}$) in an agitated bath. Feature a coiled heating element to concentrate heat at the bottom of the vessel. Heaters include a 6-ft. three-wire cord; 115 VAC models include a plug.

www.electrolux.com.mk

Satisfying your Search...

...to customize a heater on this page to your application, enter the Catalog Number into the online "Catalog Search" box, click "Go", then click on "More Info."

Select an immersion heater according to the wattage you require. The following equation is a conservative guide to help you determine the wattage required for your application.

$$\text{For water: kW} = \frac{\text{Gallons} \times \text{temperature rise } (^\circ\text{F})}{325 \times \text{heat-up time (hours)}}$$

OR

$$\text{kW} = \frac{\{1 [\text{Gallon}] = 1.785 [\text{litres}]\} \times \{1^\circ\text{C} = (5/9) \times (^\circ\text{F} - 32)\}}{325 \times t [\text{h}]}$$



Specifications & Ordering Information

Key letter	Catalog number	Watts	VAC	Approximate Immersion depth	Heated area	Temperature range	Heater style	Shpg wt lb (kg)	Price				
A	A-03046-20	500	115	2 1/4"	3 1/2" dia	Ambient to 212°F (100°C)	Loop	2 (0.9)					
B	A-03046-00			5"	5 1/2" L		Short rod						
A	A-03046-22		230	2 1/4"	3 1/2" dia		Loop						
D	A-03046-02			5"	5 1/2" L		Short rod						
C	A-03046-40	1100	115	2 1/4"	8 3/4" L		Ambient to 212°F (100°C)	Flat	3 (1.4)				
D	A-03046-50			18 1/2"	20" L			Long rod					
C	A-03046-42		230	2 1/4"	8 3/4" L			Flat					
D	A-03046-52			18 1/2"	20" L			Long rod					
D	A-03046-04	1100	115	5"	6" L			Ambient to 212°F (100°C)	Long rod	2 (0.9)			
D	A-03046-54			18 1/2"	20" L								
D	A-03046-06		230	5"	6" L								
D	A-03046-56			18 1/2"	20" L								
E	A-03052-20 A-03052-40	1500	115	3"	7" dia 10 1/2" dia	Ambient to 250°F (121°C)			Loop	4 (1.9) 4 (1.9)			
E	A-03052-10 A-03052-30 A-03052-50	1000 1000 1500	115	5"	7" dia 10 1/2" dia 13" dia				Loop	4 (1.8) 5 (2.3) 5 (2.3)			
F	A-03047-10 A-03047-12	1000			115 230				5"	7" dia	Loop	4 (1.8)	
F	A-03047-30 A-03047-32	1000			115 230					10 1/2" dia			
F	A-03047-50 A-03047-52	1500	115 230	13" dia									
G	A-03049-00 A-03049-52	550	115 230	4"	2 1/2" dia		Beaker			2 (0.9)			
H	A-03049-50 A-03049-52	550	115 230	3"	4 3/4" dia		Flat		3 (1.4)				

Ovo je crtež e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuje, umozuova niti kopira bez soglasnost od Elctroluks vo sprotivno se snosat posledici vo smislana clenovite 163 i 164 od kvincioti zakon R.M. (povreda na avtorsko pravo)

Браќа Мингови бр.18, Стара Царница Битола. Г.Т.Ц.Бунјаковец Скопје
Тел/Факс: 047/203-900; 203-330; 070/237-108
Тел/Факс:02/329 8 130;070/237 198

www.elektroluks.com.mk, www.electrolux.com.mk, electrolux@mt.net.mk

Electroluks is registered trademark of Elektroluks companies in Macedonia and other countries